



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF23312-24B	x = 0.287 y = 0.284	1100 @ 0°C	618	6 ± 1	50,000 ± 20%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>			<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- REF.</p> <p>2 PL +/- REF.</p> <p>ANGLE +/- 0</p>		<p><b>JKL</b> COMPONENTS CORPORATION</p>						
<p>REV. NO.</p> <p>DESCRIPTION/ECO NUMBER</p> <p>APPVD DATE</p>			<p>DRAWN BY</p> <p>L. WENGSTROM</p> <p>APPVD BY</p> <p>L.R.</p> <p>DATE</p> <p>11/12/08</p>		<p>SIZE</p> <p><b>A</b></p>	<p>FSCM NO.</p> <p><b>55335</b></p>	<p>DRAWING NO.</p> <p><b>BF23312-24B</b></p>	<p>RELEASED DATE</p> <p>2/21/07</p>	<p>REVISION DATE</p> <p>11/12/08</p>	<p>REV. NO.</p> <p><b>C</b></p>	<p>SHEET</p> <p>1 OF 1</p>
			<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>		<p>SCALE</p> <p>NONE</p>						